



BECKER

*Family Owned
Since 1885*

VT, KVT, VTFL SERIES OIL-FREE VACUUM PUMPS



Becker 100% Oil-Free Rotary Carbon Vane Vacuum Pumps

Becker oil-free vacuum pumps are designed to operate on a continuous duty basis at any vacuum level from open flow to 27" Hg., depending on the series. All Becker oil-free pumps utilize self-lubricating, graphite composite vanes, specifically engineered for Becker pumps. No oil to change and only minimal maintenance is required. Each pump comes with a built-in inlet filter, vacuum relief valve and vibration isolators as standard equipment.

VT Series

Model	Horsepower	CFM @ Open Flow	Max. Vacuum (Inches Hg)	Noise Level (dBA)
VT 4.4	0.289	2.8	25	61
VT 4.8	0.59	5.4	25	61
VT 4.10	0.6	7.1	25	62
VT 4.16	0.94	11	25	64
VT 4.25	1.2	17.7	25	67
VT 4.40	2.0	28	25	72



KVT Series

Model	Horsepower	CFM @ Open Flow	Max. Vacuum (Inches Hg)	Noise Level (dBA)
KVT 3.60	3	39	27	73
KVT 3.80	5	46	27	75
KVT 3.100	5	66	27	77
KVT 3.140	7.5	91	24	79



VTFL Series

Model	Horsepower	CFM @ Open Flow	Max. Vacuum (Inches Hg)	Noise Level (dBA)
VTFL 2.200	7.5	128	24	77
VTFL 2.250	8.9	169	24	79
VTFL 2.250 SK	10	174	27	79
VTFL 2.400	15	270	24	79
VTFL 2.500	25	336	22	80



Features

- 100% oil-free
- Continuous duty rated
- Quiet operation
- Compact design
- Low maintenance

Benefits

- No oil or water
- No cycling times
- No silencer enclosures needed
- Small footprint for space savings
- Field serviceable reduces downtime

Applications

- Medical/surgical
- Packaging
- Robotics/pick and place
- Material handling
- Vacuum hold down
- Printing

We are Ready to Help! Sales and Service for USA, Canada, and Mexico

Call 888-633-1083 or go to www.beckerpumps.com

100 East Ascot Lane • Cuyahoga Falls, Ohio 44223



**Order Becker Genuine Parts
Online 24/7**

www.beckerpumps.com/shop