

FEATURES AND BENEFITS

STANDARD EQUIPMENT

- NEMA-1 starter with control power transformer (shipped loose)
- Premium efficient ODP motor
- Constant speed control
- V-belt drive with multi-groove flywheel
- Large metal intake filter silencers
- OSHA-approved enclosed belt guard
- C-100 and C-150 — Pressure lubricated with Centro-ring™ oil system
- C-200, C-260 and C-300 — Pressure lubricated with gear type oil pump to include full flow oil filter, oil pressure gauge and low oil pressure shutdown switch

OPTIONAL EQUIPMENT

- Auto start/stop control
- Dual control
- Low oil shutdown on C-100 and C-150 models
- NEMA-1 high discharge air temperature shutdown
- NEMA-1 high interstage air temperature shutdown
- NEMA-4 control panel enclosure
- TEFC motor



TECHNICAL DATA

CW SERIES — SINGLE-STAGE

Low Pressure (30-70 PSIG)

MODEL	HP	CFM @ 40 PSI	CFM @ 70 PSI	DIMENSIONS L×W×H	WEIGHT (LBS)
CW-100S-16	40	N/A	N/A	81×45×47	1950
CW-200S-17	50	346	268	82×43×53	2720
CW-200S-18	60	N/A	297	82×43×53	3000
CW-300S-19	75	562	N/A	92×57×75	3500
CW-300S-20	100	676	530	92×57×75	3700
CW-300S-21	125	N/A	639	92×57×75	3950

CW SERIES — TWO-STAGE

Medium Pressure (100-150 PSIG)

MODEL	HP	CFM @ 100 PSI	CFM @ 125 PSI	CFM @ 150 PSI	DIMENSIONS L×W×H	WEIGHT (LBS)
CW-100-16	40	172	165	149	81×45×47	1950
CW-200-17	50	240	219	206	82×43×53	2720
CW-260-18	60	259	248	237	82×43×53	3000
CW-300-19	75	363	321	303	92×57×75	3500
CW-300-20	100	482	438	413	92×57×75	3700
CW-300-21	125	505	491	475	92×57×75	3950

High Pressure (175-250 PSIG)

MODEL	HP	CFM @ 200 PSI	CFM @ 250 PSI	DIMENSIONS L×W×H	WEIGHT (LBS)
CW-150H-16	40	122	117	81×45×47	1925
CW-150H-17	50	154	146	82×43×53	1975
CW-260H-17	50	191	169	85×40×51	2720
CW-260H-18	60	218	205	82×43×53	3000
CW-300H-20	100	345	323	92×57×75	3700
CW-300H-21	125	437	406	92×57×75	3950